





HARDENER FOR MASTON 2K EPOXY PRIMER 180ML



COVERAGE


VERY HARD
SURFACE

GLOSSY FINISH
SURFACE

WEATHER-
PROOF

Hardener for Maston 2K Epoxy Primer 180ml PRIMER: MASTON 2K EPOXY PRIMER is suitable for steel surfaces and acid-resistant steel, zinc and aluminum surfaces. Resistant to heavy wear, oil, grease, solvents and chemicals.

APPLICATION TIME : Must be used within 2 hours when hardener is mixed in.

APPLICATION: The surface must be sanded or roughened and cleaned well. Use a degreaser for cleaning. Paint 2 layers maximum. The temperature of the object to be painted and the air must be above 10 ° C. Mix the paint thoroughly. Use thinner if necessary (with Maston EPX thinner). When painting with a spray gun, the nozzle recommendation is 0.013 - 0.019". A roller or brush can also be used for small objects.

BINDER: Other

DEGREE OF GLOSS (DIN 67530 60 °):
semi-gloss 40-60 gloss units


HEAT RESISTANCE: 150°C

STORAGE STABILITY: 36 months

SIZE: other , 180ml

SALES QTY:
other: 6 pcs
180ml: 6 pcs

MATERIAL



METAL



CARDBOARD



IN AND OUT


CLEAN WITH DEGREAS-
ER


20% TO 80% MIX



ADD THINNER 10-30%



OVERPAINT



TOUCH DRY



FINAL DRYING



FINAL HARDNESS


EPOXY
SOLVENT BASED

MASTON Hardener for Maston 2K Epoxy Primer 180ml

Art. No.	MASTON Hardener for Maston 2K Epoxy Primer 180ml	Color	Barcode
20080005-EU	Hardener for Maston 2K Epoxy Primer 180ml		6412490033019

MASTON Hardener for Maston 2K Epoxy Primer 180ml

Art. No.	MASTON Hardener for Maston 2K Epoxy Primer 180ml	Color	Barcode
20080005	Hardener for Maston 2K Epoxy Primer 180ml		6412490016302