

www.maston.fi





## **QUICK FILLER 200ML**



USE 5-50DEGREES



1-2H TOUCH DRY FILLER



SAND P100-P120



STORE IN +5-+50°C

Maston Quick Filler is a white, ready-mixed, extra fine hand filler for woodwork. Use the product when filling frames doors, hatches and suchlike indoors. Good adhesive, strength and building properties make the smoothed surface an excellent base coat for joinery and gloss paint.

INSTRUCTIONS Apply by hand on clean, dry and firmly attached surfaces at a minimum temperature of +5°C. The filled surface is sanded when it has dried. Use sandpaper with particle size 100-120. Eye protection and a dust mask are recommended when sanding. Dust off before the next treatment. Filled surfaces should be primed before wallpapering.

Tools are to be cleaned in water. Large volumes of waste can be deposited as normal refuse at municipal refuse facilities. The plastic in the packaging is recyclable and must therefore be taken to the appropriate recycling point or municipal recycling plant

Drying time  $\pm 20^{\circ}$ C: 1 - 2 h The drying time is dependent on substrate, layer thickness, temperature, air humidity etc.

Coverage: 0.5 mm thin coat plastering = approx. 0.5 litre/m2.

Working temperature: +5 - +50 ° C.

BINDER: Latex co-polymer

**HEAT RESISTANCE:** 50°C

STORAGE STABILITY: 24 months

SIZE: 200ml

**SALES QTY:** 200ml: 12 pcs





## **MASTON Quick Filler 200ml**

Art. No.	MASTON Quick Filler 200ml	Color	Barcode
839701	Quick Filler 200ml	$\bigcirc$	6412498397014

