

www.maston.fi



## **STONECHIP**







ING

25 CM

SPRAY DISTANCE

15 MIN

TIME BETWEEN LAY-

ERS

MASTON STONECHIP SPRAY provides effective protection for car parts that are susceptible to stone chipping. Thanks to its rubbery consistency, it is an excellent protector against chipping and rusting. It also has a soundproofing effect. Maston Stonechip can be painted over with most car paints.

### HARDNESS 2 SOFT



**CLEAN WITH BRUSH** 











3 MIN

SHAKE



OVERPAINT

RUBBER SOLVENT BASED

#### STORAGE STABILITY: 60 months

**SIZE:** 500ml

SALES QTY: 500ml: 6 pcs

#### **USAGE INSTRUCTIONS:**

Instructions: Carefully clean the painted surface you wish to treat. Cover all surfaces that do not require treatment. Shake the container for approx. 3 minutes before use. Spray from a distance of approx. 30 cm.

Spray several thin layers, letting the paste dry in between sprayings. This will give an even and protective result. Shake the container during the process to keep the paste liquid and spreadable. Clean nozzle after use: turn container upside down and press the atomizer until only propellant gas / air comes out.

For stain removal we recommend Maston Thinner. Drying time at +20 °C: touch-dry in approx. 30-60 min., ready for repainting in 1-2 h.

#### **RECOAT:**

Repainting: Before repainting, ensure that the paste is completely dry and properly adhered to the treated surface







# **MASTON Stonechip**

Art. No.	MASTON Stonechip	Color	Barcode
4150502	Spray Stonechip coating STH-50 Grey Auto 500ml		6412490000189
4150501	Spray Stonechip coating STH-50 Black Auto 500ml		6412490000172
4150503		0	6412490040147
4150501-EU	Spray Stonechip coating Black 500ml		6412490034269

