




UNDERBODY COATING UBC-11 AUTO 1L (SCREW-TOP JAR)



THEORETICAL COVERAGE



RUST STOP



FLEXIBLE




HIGH FILLIG POWER



CLEAN WITH BRUSH



3 MIN SHAKE



LAYERS



30 MIN TIME BETWEEN LAYERS



75 MIN TOUCH DRY



3,5 H FINAL DRYING



CLEAN WITH CLOTH AND SOLVENT

Maston Underbody coating is a quick-drying bitumen-based protector for your car's chassis. It is flexible, hard-wearing, and provides excellent protection against rust. Instructions: Clean the surface carefully, it should be clean, dry and free of grease. Cover all surfaces that do not require treatment. Shake the container for approx. 30 minutes before use. Working pressure: bar 4-5. Spray from a distance of approx. 30 cm. Spray several thin layers, letting the paste dry in between sprayings. This will give an even and protective result. About 30 minutes in between the layers. Shake the container during the process to keep the paste liquid and spreadable. Coverage 2m². Drying time at +20 °C: Dry to touch after 75 minutes, completely dry after 3,5 hours. Stain removal we recommend Maston Thinner.

STORAGE STABILITY: 60 months

SIZE: 1l

SALES QTY:
1l: 12 pcs

MASTON Underbody coating UBC-11 Auto 1L (screw-top jar)

Art. No.	MASTON Underbody coating UBC-11 Auto 1L (screw-top jar)	Color	Barcode
4150110		○	6412490000134