



SPRAY UNDERBODY COATING AUTO 500ML



RUST STOP



FLEXIBLE



HIGH FILLIG POWER



SOUND ABSORB-ING

Maston Underbody coating is a quick-drying bitumen-based protector for your car's chassis. It is flexible, hard-wearing, and provides excellent protection against rust. Instructions: Clean the surface carefully. Cover all surfaces that do not require treatment. Shake the container for approx. 3 minutes before use. Spray from a distance of approx. 30 cm. Spray several thin layers, letting the paste dry in between sprayings. This will give an even and protective result. Shake the container during the process to keep the paste liquid and spreadable. Clean nozzle after use: turn container upside down and press the nozzle until only propellant comes out. Drying time Approx 2 h at +20 °C. For stain removal we recommend Maston Thinner.

HARDNESS



STORAGE STABILITY: 60 months

SIZE: 500ml

SALES QTY:
500ml: 6 pcs



CLEAN

CLEAN WITH BRUSH




3 MIN SHAKE



25 CM

SPRAY DISTANCE



4 LAYERS

1-4 LAYERS



CLEAN UP



15 MIN

TIME BETWEEN LAYERS



2H

FINAL DRYING



CLEAN WITH CLOTH AND SOLVENT



BITUMEN SOLVENT BASED

MASTON Spray Underbody coating Auto 500ml

Art. No.	MASTON Spray Underbody coating Auto 500ml	Color	Barcode
4150100	Spray Underbody coating Auto 500ml	○	6412490000127
4150100-EU	Spray Underbody coating Auto 500ml	○	6412490034252