



STONECHIP



RUST STOP


HIGH FILLING
POWER


FLEXIBLE



SOUND ABSORB-
ING

HARDNESS



CLEAN WITH BRUSH



3 MIN
SHAKE

25 CM
SPRAY DISTANCE


LAYERS



CLEAN UP


TIME BETWEEN LAY-
ERS


TOUCH DRY


ALL PAINTS 3H
OVERPAINT

RUBBER
SOLVENT BASED

MASTON STONECHIP SPRAY provides effective protection for car parts that are susceptible to stone chipping. Thanks to its rubbery consistency, it is an excellent protector against chipping and rusting. It also has a soundproofing effect. Maston Stonechip can be painted over with most car paints.





Instructions: Carefully clean the painted surface you wish to treat. Cover all surfaces that do not require treatment. Shake the container for approx. 3 minutes before use. Spray from a distance of approx. 30 cm. Spray several thin layers, letting the paste dry in between sprayings. This will give an even and protective result. Shake the container during the process to keep the paste liquid and spreadable. Clean nozzle after use: turn container upside down and press the atomizer until only propellant gas / air comes out. For stain removal we recommend Maston Thinner. Drying time at +20 °C: touch-dry in approx. 30-60 min., ready for repainting in 1-2 h. Repainting: Before repainting, ensure that the paste is completely dry and properly adhered to the treated surface

STORAGE STABILITY: 60 months

SIZE: 500ml

SALES QTY:
500ml: 6 pcs

MASTON Stonechip

Art. No.	MASTON Stonechip	Color	Barcode
4150502	Spray Stonechip coating STH-50 Grey Auto 500ml		6412490000189
4150501	Spray Stonechip coating STH-50 Black Auto 500ml		6412490000172
4150503			6412490040147
4150501-EU	Spray Stonechip coating Black 500ml		6412490034269