




## SPRAY FILLER



COVERAGE


HIGH FILLING  
POWER


RUST STOP



STRONG BOND

MASTON SPRAY FILLER compounds of car refinish filler, acrylic binder and additives. It has good filling power, it levels fast and dries quickly. Easy to sand, but can also be painted with overcoat directly, no sanding needed. Due to the acrylic base Maston fillers and primers are compatible with most of the overcoats, also with synthetic or nitro based primers. Suitable for metal, aluminium and wood.

New layer can be applied wet-on-wet or wet-on dry. Easy to sand, for sanding after drying we recommend wet-sandpapers grain, final grain 400-600.

### HARDNESS



### DEGREE OF GLOSS (DIN 67530 60 °):

matt 0-25 gloss units

**STORAGE STABILITY:** 60 months

**SIZE:** 400ml

### SALES QTY:

400ml: 0 pcs

### RECOAT:

always, 5 minutes in between layers


3 MIN  
SHAKE

15 CM  
SPRAY DISTANCE


SPRAY PATTERN


5 MIN  
TIME BETWEEN LAY-  
ERS

SEVERAL LAYERS  
LAYERS


CLEAN UP


30 MIN  
TOUCH DRY

FINAL HARDNESS  
24H

ACRYL  
SOLVENT BASED

## MASTON Spray filler

Art. No.	MASTON Spray filler	Color	Barcode
4780100	Spray sprayfiller 400ml		6412490002503