



SPRAY AUTOACRYL PRIMER



COVERAGE



QUICK DRYING



VERY HARD SURFACE



UV-PROOF

Maston AutoACRYL is high quality acrylic primer for metal parts, hard plastic parts and rims. Excellent coverage, quick drying time, smooth surface and durable gloss. Instructions: Polish the surface. Prime metal surfaces with primer and plastic surfaces with plastic primer if necessary. The surface has to be clean, dry and free of any grease, wax or silicone.

BINDER: Acryl

DEGREE OF GLOSS (DIN 67530 60 °):
matt 0-25 gloss units

HEAT RESISTANCE: 120°C

STORAGE STABILITY: 60 months

SIZE: 500ml

SALES QTY:
500ml: 6 pcs

USAGE INSTRUCTIONS:

Shake can for at least 2-3 minutes also occasionally during painting. Paint a test patch on invisible area first. Start spraying outside the object. Spray at distance of about 25 cm from surface and move the spray slowly on the object. Spray a thin layer first to improve adhesion. Let dry between layers for 3-5 minutes. Thereafter apply 2-3 thin cross layers on the surface and let dry. Repeat if necessary. Drying time: Touch-dry 10-20min. Totally dry 24 hours. Clean the nozzle by turning the can upside down and spray until only propellant comes out.


HARDNESS



SHAKE



25 CM
SPRAY DISTANCE




SPRAY PATTERN



CLEAN UP



5MIN
TIME BETWEEN LAYERS



LAYERS



15MIN
TOUCH DRY



24H
FINAL DRYING



SOLVENT BASED ACRYL
SOLVENT BASED

MASTON Spray AutoACRYL Primer

Art. No.	MASTON Spray AutoACRYL Primer	Color	Barcode
4305180	Spraypaint AutoACRYL Grey Primer 500ml		6412490024987
4305190	Spraypaint AutoACRYL Red Primer 500ml		6412490024994