


www.maston.fi



## SPRAY AUTOACRYL CLEAR COAT







24H

FINAL DRYING

SOLVENT BASED ACRYL SOLVENT BASED

Maston AutoACRYL lacquer is high quality acrylic clear coat for metal parts, hard plastic parts and rims. Excellent coverage, quick drying time, smooth surface and durable gloss. Instructions: Polish the surface. Prime metal surfaces with primer and plastic surfaces with plastic primer if necessary. The surface has to be clean, dry and free of any grease, wax or silicone.

## BINDER: Acryl

DEGREE OF GLOSS (DIN 67530 60 °): gloss 80-100 gloss units

HEAT RESISTANCE: 120°C

STORAGE STABILITY: 60 months

SIZE: 500ml

SALES QTY: 500ml: 6 pcs

## **USAGE INSTRUCTIONS:**

Shake can for at least 2-3 minutes also occasionally during painting. Paint a test patch on invisible area first. Start spraying outside the object. Spray at distance of about 25 cm from surface and move the spray slowly on the object. Spray a thin layer first to improve adhesion. Let dry between layers for 3-5 minutes. Thereafter apply 2-3 thin cross layers on the surface and let dry. Repeat if necessary. Drying time: Touch-dry 10-20min. Totally dry 24 hours. Clean the nozzle by turning the can upside down and spray until only propellant comes out.









## MASTON Spray AutoACRYL Clear Coat

Art. No.	MASTON Spray AutoACRYL Clear Coat	Color	Barcode
4303320	Spraypaint AutoACRYL Clear Coat 500ml	$\bigcirc$	6412490024970

